

# Conpro Plug

**Hand or trowel applied,  
single component,  
fast setting  
hydraulic cement.**

**WHERE TO USE**  
**Stop running water,  
pressure leaks and seepage.**  
**Seal concrete and clay pipe joints,  
fill cracks and voids.**

## PERFORMANCE CHARACTERISTICS

### Stops pressure leaks

- Fast setting – changes from a mortar-like consistency to hardened state in about 60 seconds.

### Expanding

- Expands as it sets.

### Seals

- Watertight seal for concrete and clay pipe connections. Forms a watertight seal for through-wall pipes and conduit in foundation walls.

### Crack repair

- Watertight repair material for static cracks.

### Easy to use

- Simply add water and mix.

### Environmentally friendly

- Water based technology, easy to use and clean up.

## SURFACE PREPARATION

- Remove loose and deteriorated material, laitance, dirt, dust, oil and any surface contaminants that will inhibit proper bond.
- Prepare a mechanical key using a hammer and chisel to notch a keyway in the area of the leak. Minimum depth of repair is 3/4 inch.
- Relieve pressure where necessary by drilling weep holes near the bottom of the wall.
- For static cracks, and at the intersection of the wall and floor slab rout the crack at least 3/4 x 3/4 inch, slightly undercutting if possible.
- Saturate substrate with clean water, (saturated surface dry/SSD).

## PRIMING

- No priming is required under normal circumstances.

## MIXING

- Pour a small amount of water into a clean vessel. Slowly add powder while mixing with gloved hand or margin trowel to a stiff mortar consistency.
- Do not re-temper.

## APPLICATION

- Scoop the material while still plastic, with a gloved hand.
- Form a ball of the material and hold until it begins to generate heat.
- Once warm, press into the hole or prepared keyway with force.
- Hold in place for 1 minute or until hard.
- Shave excess material from surface.
- Cold water will slow set, warm water will accelerate set.
- Apply *Conpro Seal* or *Conpro Super Seal* for additional waterproof protection.

## CURING

- No curing procedures are required.

## CLEAN UP

- Clean tools and equipment with water immediately after use. Cured material must be removed mechanically.

# Conpro Plug

## COVERAGE/YIELD

- 0.50 ft.<sup>3</sup>/50 lbs.

## PRODUCT HANDLING

### Packaging

- 10 lbs. and 50 lbs. plastic pails.

### Shelf Life

- 18 months when properly stored.

### Storage

- Transport and store in cool, clean, dry conditions in unopened containers.
- High temperature or high humidity will reduce shelf life.

## LIMITATIONS

- Do not apply unless substrate and ambient temperature can be maintained at a minimum of 40°F for 24 hours. Refer to ACI Cold Weather Application Guidelines.
- Cold mixing water and low temperature will retard set. Hot water and high temperature will accelerate set.
- Do not add more water than specified.
- Avoid overworking material during placement.

## HEALTH AND SAFETY

- Product is alkaline.
- Do not ingest.
- Avoid breathing dust.
- Avoid contact with skin and eyes.
- Refer to Material Safety Data Sheet (MSDS) for additional information.

## FIRST AID

- In case of skin contact, wash thoroughly with soap and water. For eye contact, flush immediately with a high volume of water for at least 15 minutes and contact a medical professional. For respiratory problems, remove person to fresh air.

## DISPOSAL

- Dispose of material in accordance with local, state or federal regulations.

## TECHNICAL DATA

Physical state and appearance		Fine, gray powder			
Base		Hydraulic cement			
pH	Wet mix	>12			
Density	Wet mix	130 lbs./ft. <sup>3</sup>			
Setting time by vicat needle	ASTM C191	Initial 4 minutes – Final 7 minutes			
Percent air by volumetric	ASTM C173	5%			
		<b>1 Hour</b>	<b>7 Days</b>	<b>14 Days</b>	<b>28 Days</b>
Compressive strength – psi	ASTM C109	1070	2210	2675	3000
Tensile strength – psi	ASTM C307		360	480	500

### FOR PROFESSIONAL USE ONLY

Conproco Corp. warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current technical data sheet if used as directed within shelf life. User determines suitability of product for use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor. January 2005.

NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. CONPROCO CORP. SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES.

**conproco**<sup>®</sup>  
CORPORATION

17 PRODUCTION DRIVE, DOVER, NEW HAMPSHIRE 03820  
TELEPHONE 800.258.3500 • FAX 603.743.5744 • WEB ADDRESS [www.conproco.com](http://www.conproco.com)